

MACHINE QUILTING WITH RULERS

April 18, 2019, 9:30 – 4:30

With Anita Chaisty

SUPPLY LIST

SEWING MACHINE IN GOOD WORKING ORDER

(MUST BE ABLE TO DROP FEED DOGS OR COVER THEM FOR MACHINE QUILTING)

***RULER FOOT FOR YOUR MACHINE (RESOURCE LIST BELOW) - must have for class!!**

THREAD - WHATEVER YOU USUALLY USE FOR MACHINE QUILTING

EXTRA SEWING MACHINE NEEDLES

FABRIC MARKING PEN

STRAIGHT QUILTING RULER - RECOMMEND A SMALL SIZE - *CREATIVE GRID 'SLIM' WILL BE AVAILABLE AT CLASS FOR \$19

SAMPLE PIECE AS DESCRIBED BELOW

QUILTING GLOVES - MAY USE QUILTING GLOVES, GARDEN GLOVES ETC THAT HAVE GRIPS, OR THE TIPS FROM PLAYTEX GLOVES OR WHATEVER YOU NORMALLY USE TO GRIP THE QUILT WHEN YOU QUILT

SUPREME SLIDER (OPTIONAL)

FABRIC AND BATTING SCRAPS OR UFO BLOCKS THAT CAN BE PRACTICED ON (OPTIONAL)

I will have a few Supreme Sliders and Quilting Gloves for sale at the class if you need.

RULER FOOT RESOURCES

You will need to know whether your machine has a low shank, high shank, or mid shank. You will find that some of the websites that sell the feet also have descriptions of the various shanks so you will know what you need.

Distributor for your Machine Make: Bernina, Janome, etc.

Sew Steady - sewsteady.com - has the Westalee foot which is very good

Nancy's Notions - also includes a list of types of shanks and what the feet do not fit.

Amazon - you will need to know the type of shank of your machine

SAMPLE PIECE

USE AT LEAST 2 FABRICS - 1 FABRIC FOR THE BLOCKS AND THE OTHER FOR SASHING AND BORDERS. FABRICS SHOULD BE SOLIDS OR TONE ON TONE SO THAT YOU CAN FOCUS ON THE QUILTING PATTERNS.

CUT 6 10 1/2" BLOCKS

CUT 2 3" x WOF STRIPS FOR SASHING

SUBCUT INTO (4) 3" X 10 1/2" STRIPS

SUBCUT IN (1) 3" X 35 1/2" FOR SASHING

BORDERS - CUT 2 STRIPS 5 1/2" 23" (CAN PIECE IF YOU WOULD LIKE SINCE THIS IS A PRACTICE PIECE)

PIECE 2 STRIPS 5 1/2" TO TOTAL 46" FOR THE TOP AND BOTTOM BORDER.

BACKING - WILL NEED 38" BY 52"

- 1. SEW SASHINGS TO RIGHT SIDE OF 4 OF THE BLOCKS.**
- 2. SEW 3 BLOCKS INTO ROWS MAKING 2 ROWS.**
- 3. SEW LONG SASHING PIECE BETWEEN THE ROWS.**
- 4. SEW ON 2 SIDE BORDERS.**
- 5. ADD THE TOP AND BOTTOM BORDERS.**
- 6. MAKE SANDWICH WITH BATTING AND BACKING. YOU CAN USE PINS, FUSIBLE BATTING, OR ADHESIVE SPRAY - WHATEVER YOU PREFER.**